

**NEW!**  
Interactive Public  
View Monitor  
Exclusively  
for Retail

## **INTERACTIVE PUBLIC VIEW MONITOR**

### **The Most Flexible and Effective Public View Monitor On the Market**



#### **It's Interactive...**

- Responds to motion and event triggers.
- Wired and wireless triggering built-in.
- Displays custom graphics linked to events.
- Programmable LED light and alarm tones.
- Features video-based motion detection.
- Enhances EAS and smart shelving systems.



22" High resolution  
widescreen LCD display

Remotely powered by low  
voltage up to 300 feet

Aids in reducing theft in  
high-shrink aisles

Promotes brand  
awareness

Connections have a unique  
"response profile" displaying  
a custom graphic or video

**Checkpoint** 

Helping Retailers Grow Profitably

# INTERACTIVE PUBLIC VIEW MONITOR

## ENGINEERED EXCLUSIVELY FOR RETAIL

Checkpoint introduced the industry first flat panel PVM in 2002, and continues to lead the market with cutting-edge features designed to maximize the value of a video security investment. Don't confuse the IPV with the wide range of public view displays on the market. This monitor was engineered exclusively for retail from the ground up. Standard features include completely automatic Day/Night/Sleep energy modes, customized on-screen graphics and remote low-voltage power.

The IPV takes advantage of the latest wide-dynamic imaging technology to display video quality worthy of your brand, and the triggering options provide an entirely new way to think about applying public view systems. Use the monitor to display a message when someone enters a high-shrink aisle. Display your store's logo until activity is detected in the area. Trigger the IPV from an EAS system, smart shelf, fire exit door, or video analytics device to further enhance the effectiveness of these systems. The possibilities are endless when you use the Interactive Public View Monitor.

### Technical Specifications:

Monitor Type:	TFT LCD
Display Size:	22" Diagonal
Pixel Format:	1680(H) x 1050(W)
Contrast Ratio:	1000:1
<b>General</b>	
Video System:	NTSC/PAL
Picture Mode:	Full Screen, PIP, Split Screen
Memory:	Three High Quality Images (Logo, Messaging, etc...)
Alarm Sounder:	Piezo with Multiple Patterns
LED Alarm Indicator:	Multiple Flash Rates
Connections:	Video In: One BNC aux input Video Out: One BNC integrated camera output Wireless Transceiver (optional) Dry Contact Inputs: 4 Power Input: Low-Voltage
Power Requirements:	30VDC via 110/220VAC Power Supply Low-Voltage Wiring: 300 ft maximum, 14AWG
Power Consumption:	Approx. 45 watts (5 watts Sleep Mode)
Dimensions:	Monitor: 22.25" W x 18.13" H x 4.0" D
Weight:	15 lb.
Mounting:	VESA FDMI Compliant 3.93 inches (100mm)

#### Integrated PIXIM™ Seawolf WDR Camera

Image Sensor: 1/3" CCD  
Active Pixels: 768(H) x 548(W)  
Resolution: 690 TV lines  
Sensitivity: 50 IRE 0.1 lux (F1.2)  
Iris: DC iris + electronic Shutter  
Lens: 2.6-6.0 mm Varifocal (F1.4)

Checkpoint Systems, Inc. is an Environmentally Committed Organization.



- LOW-VOLTAGE POWER
- AUTO NIGHT MODE
- EXTENDED LIFE DESIGN
- ROHS COMPLIANT

*Specifications and designs are subject to change without notice.*

### Color Options:



Silver



Black



White

### Want More Information:

Click or scan with your smart phone and instantly get more information on Checkpoint's NEW Interactive Public View Monitor.



#### Checkpoint Systems, Inc.

101 Wolf Drive, P.O. Box 188  
Thorofare, NJ 08086

[www.CheckpointSystems.com](http://www.CheckpointSystems.com)

Tel.: 800-257-5540 or 856-848-1800

E-mail: [marketingleads@checkpt.com](mailto:marketingleads@checkpt.com)

**Checkpoint**

Helping Retailers Grow Profitably